



CINEMA PERFORMANCE IN YOUR HOME

Harness decades of cinema sound research and development with the high performance HT-50 surround sound system from Klipsch. Comprised of four miniature speakers and a low-profile center channel the Klipsch HT-50 home theater system incorporates decades of class-leading engineering expertise. In fact, it applies the same cutting-edge technology that's found in our professional cinema products for immersive, dynamic, cinematic sound with pristine detail, power, and intelligibility.

EXCLUSIVE XT MICRO-TRACTRIX™ HORN TECHNOLOGY

Horns have long been the cornerstone of Klipsch loudspeaker design, from our professional cinema to our ultra-premium home theater products. Our exclusive XT Micro-Tractrix® Horn Technology used in the HT-50 delivers the most impressive high-end response and greater extension, enhanced imaging and powerful dynamics. This creates the cleanest, most natural sound possible.

LTS TWEETER TECHNOLOGY

A Linear Travel Suspension (LTS) aluminum tweeter design minimizes distortion for enhanced, detailed high frequency performance. LTS tweeters have been a hallmark of the Klipsch Reference series product lines, making it a core component of some of the best speakers in the world.

HIGH-PERFORMANCE WOOFERS

The HT-50 utilizes high-excursion aluminum woofer cones, which have been designed for maximum bass output that blends seamlessly into the sound of your favorite movies, TV shows and video games. The aluminum cone structure provides minimum distortion, even at high volumes, while a robust motor structure means maximum power handling and efficiency - for louder, more dynamic sound.

COMPACT, HIGH QUALITY CABINET DESIGN

Every piece of the HT-50 system comes housed in our exclusive AcoustiComp® cabinets, ensuring a solid foundation to channel flawless sound. AcoustiComp is a high-density material used extensively in both Professional Cinema and Music speakers. It is not only durable, it is so solid that cabinet resonance is never an issue - meaning you get punchy, accurate sound every time. The low-profile design of both the HT-50 satellites and center channel speaker better-match today's thinner and more aesthetic TV's whether stand or table placed or mounted on the wall with the integrated brackets.

SPECIFICATIONS

SYSTEM TYPE	5.0 Surround Sound System
ENCLOSURE TYPE	Bass-reflex via rear-firing port
FREQUENCY RESPONSE	Satellite: 120Hz-23kHz Center: 125Hz-23kHz
HIGH-FREQUENCY HORN	90° x 40° XT MicroTractrix Horn
TWEETER	One 0.75-inch (1.9 cm) neodymium magnet compression driver
MIDRANGE	One 3.5-inch (8.9 cm) magnetically shielded woofer
CROSSOVER FREQUENCY	Satellite: 3700Hz; Center: 3100Hz
MOUNTING	Satellite: Base swivels for on-wall mounting via keyholes Center: Threaded insert
NOMINAL IMPEDANCE	8-ohms compatible
POWER HANDLING	Satellite: 50 watts (200 watts peak) Center: 75 watts (300 watts peak)
SENSITIVITY	Satellite: 91dB@2.83 volts/1 meter Center: 94dB@2.83 volts/1 meter
DIMENSIONS (HxWxD)	Satellite: 8.3" x 5" x 6.3" (21.1 cm x 12.7 cm x 16 cm) Center: 5" x 12" x 6" (12.7 cm x 30.5 cm x 15.2 cm)
WEIGHT	Satellite: 3.5 pounds (1.6 kg) Center: 5.5 pounds (2.5 kg)