

CS-16C

6.5" In-Ceiling Speaker



HIGH VALUE MEETS HIGH DESIGN

The all new CS-16C delivers excellent performance, reliability and style at an affordable price. With all new minimum bezel grille, with square grille available (sold separately), the CS-16C provides exceptional performance with a contemporary design that is well suited for even the most luxurious of interior living spaces.

SLIMTRIM™ GRILLE

With the flat, magnetic grille, the visible frame size is reduced by 90% and grille depth is reduced by 80% over competitive designs, for a more edge-to-edge consistent look that blends in with the ceiling or wall more attractively. The powercoated steel grille attaches tightly and securely with ease to virtually eliminate resonant distortion. Square grille also available soon (sold separately).

POLYMER DOME TWEETER

The low-resonance, 1" polymer dome tweeter recreates high frequencies with reduced distortion and balanced, wide dispersion.

POLY WOOFER

Dense, yet lightweight, poly cone reproduces authoritative bass.

COMPATIBLE WITH THE KLIPSCH IK-650-C INSTALL KIT

For increased mounting flexibility and pre-install marking during new construction.

COMPATIBLE WITH THE KLIPSCH ME-650-C FIRE-RATED SPEAKER ENCLOSURE

For meeting building codes and/or reduction of transferred sound between rooms.

SPECIFICATIONS	
FREQUENCY RESPONSE	57Hz - 20kHz (+/- 3dB)
POWER HANDLING	35 RMS / 140 Watts Peak
RECOMMENDED AMP POWER	100W
SENSITIVITY	91 dB @ 2.83V / 1 Meter
NOMINAL IMPEDANCE	8 Ohms Compatible
HIGH FREQUENCY DRIVER	1" (2.5cm) Polymer Dome Tweeter
LOW FREQUENCY DRIVER	6.5" (16.5cm) Poly Woofer
ENCLOSURE TYPE / MATERIAL	ABS/Infinite Baffle, Front Flush With Wall
WIRE GAUGE RECOMMENDED	12 Gauge
DIAMETER	9.5" (24.13cm)
CUTOUT DIMENSIONS	8.3" (21cm)
MOUNTING DEPTH	4.2"
INSTALLATION KIT	IK-650-C (Sold Separately)
FIRE RATED ENCLOSURE	ME-650-C (Sold Separately)
PRODUCT WEIGHT	7.2 lbs
BUILT FROM	2016



3502 WOODVIEW TRACE INDIANAPOLIS, IN 46268 | KLIPSCH.COM